





版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



PCB PALOUT

P=7.62mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	17.24	24.86	32.48	40.10	47.72	55.34	62.96	70.58	78.20	85.82	93.44	101.06
B	7.62	15.24	22.86	30.48	38.10	45.76	53.34	60.96	68.58	76.20	83.82	91.44
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	108.68	116.30	123.92	131.54	139.16	146.78	154.40	162.02	169.74	177.26	184.88	
B	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.74	175.26	

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/15A	320V/24A
压线范围 (Wire Range)	22~14AWG	2.5mm ²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	

产品命名编码:

(Product Number Code):

GSA25C-7.62-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求
(Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

- 1: 单倍间距 (Single Pitch)
- 2: 双倍间距 (Double Pitch)

- 1: 绿色 (Green)
- 2: 蓝色 (Blue)
- 3: 黑色 (Black)
- 4: 灰色 (Grey)
- 5: 橙色 (Orange)
- 6: 红色 (Red)
- 7: 透明色 (Transparent)
- 8: 白色 (White)
- 9: 黄色 (Yellow)
- Y: 多种颜色 (Mixed Color)

宁波高胜电子有限公司 NINGBO GOOSVN ELECTRONIC CO.,LTD	公差范围 (Tolerance Range)	
	150~	±1.50
型号 (Type): GSA25C-7.62-XXP-1Y-00A (H)	60~150	±1.00
核准 (Approval):	30~60	±0.60
	6~30	±0.40
审核 (Audit):	0~6	±0.25
	角度 (Angle): X	±2°
设计 (Design):	XX	±1°
	比例 (Scale): FULL	版次 (Version): T0